BMW Media Information

2/2013

Valid from 3/2013

## Specifications. BMW 3 Series Touring. 325d



		BMW 325d Touring
Body		
No. of doors/seats		5/5
LW/H 1) (unladen)	mm	4624 / 1811 / 1429
Wheelbase	mm	2810
Front/rear track		1531 / 1572
Ground clearance	mm	140
	mm	
Turning circle	m	11.3
	approx. I	57
Cooling and heating system reservoir capacity Engine oil capacity <sup>2)</sup>	- 1	7.0 5.2
	1	-
Weight, unladen (DIN/EU)	kg	1540 / 1615
Payload (DIN)	kg	550
Permitted total weight	kg	2090
Permitted axle load, front/rear	kg	940 / 1215
Permitted trailer load (12%) braked/unbraked	kg	1800 / 750
Permitted roof load/trailer download	kg	75 / 75
Luggage compartment capacity	1	495 – 1500
Aerodynamic drag	c <sub>c</sub> x A	0.31 x 2.20
Engine		
Type/no. of cylinders/valves		in-line / 4 / 4
Engine technology		BMW TwinPower Turbo technology: multi-stage charging with two turbochargers, common-rail direct fuel injection with piezo injectors, maximum injection pressure 1800 bar
Effective capacity	CC	1995
Stroke/bore	mm	90.0 / 84.0
Compression ratio	:1	16.5
Fuel type		Diesel
Output	kW/hp	160 / 218
at rpm	min <sup>-1</sup>	4400
Torque	Nm	450
at rpm	min <sup>-1</sup>	1500 – 2500
αιτριτι	111111	1300 - 2300
Electrical		
Battery charge/location	Ah/–	90 / luggage compartment
Alternator current/output	A/W	180 / 2520
Driving Dynamics and Safety		
Front suspension		Aluminium double-joint spring-strut axle with displaced camber, small positive steering roll radius, transverse force compensation, anti-dive
Rear suspension		Five-link axle in lightweight construction
Front brakes		Single-piston floating-calliper disc brakes
Rear brakes		Single-piston floating-calliper disc brakes
Driving stability systems		As standard: DSC incl. ABS, ASC and DTC (Dynamic Traction Control), CBC Cornering Brake Control, DBC Dynamic Brake Control, brake drying function, fading compensation, start-off assist
Safety equipment		As standard: driver and front-seat passenger airbags, driver and front-seat passenger side airbags, front and rear head airbags, three-point automatic seatbelts for all seats, seatbelt tensioners and seatbelt force limiters in front seats, crash sensors, tyre defect indicator
Steering		Electromechanical rack-and-pinion power steering (EPS) with Servotronic function, optional: Variable Sport Steering
Overall steering ratio	:1	15.1
Overall steering ratio Front/rear tyres	:1	, , , , , , , , , , , , , , , , , , ,

## **BMW** Media Information

2/2013

Valid from 3/2013

## Specifications. BMW 3 Series Touring.

		BMW 325d Touring
BMW ConnectedDrive		
Comfort		Optional: BMW Assist including information service, remote functions, Real Time Traffic Information, BMW TeleServices, mobile device integration
Information and entertainment		Optional: Internet connectivity, BMW Online including parking information, country information, Google business search, news, real-time weather, BMW Routes, office functions, Bluetooth audio streaming, online music title update, apps
Safety		Optional: Adaptive Headlights with turning lights, variable light distribution and adaptive headlight range adjustment, high beam assistance, park distance control, rear view camera, Surround View incl. Side View and Top View, BMW Head-Up Display, cruise control with brake function, Parking Assistant, Lane Chance Warning, Lane Departure Warning with Collision Warning, speed limit and no passing information, Active Protection, extended emergency call
Transmission		
Type of gearbox		6-speed manual
Gear ratios I	:1	
II	:1	2.248
	:1	
IV	:1	
V	:1	
VI	:1	
R	:1	
Differential ratio	:1	3.462
Performance		
Weight-to-power ratio (DIN unladen)	kg/kW	9.6
Specific power output	kW/l	80.2
Acceleration 0–100 km/h	sec.	6.9
0–1,000 m	sec.	27.0
in 4th/5th gear 80-120 km/h	sec.	5.517.2
Max. speed	km/h	238
BMW EfficientDynamics		
BMW EfficientDynamics Featuincluded as standard	ıres	Brake Energy Regeneration, electromechanical power steering, Automatic Start/Stop function, gear shift indicator, ECO PRO mode, intelligent lightweight construction, on-demand operation of ancillary units, map-regulated oil pump, air flap control, differential with optimized-warm-up behaviour, tyres with reduced rolling resistance
Fuel consumption (EU)		
Urban	l/100 km	6.4
Extra-urban	I/100 km	4.3
Total	l/100 km	
CO <sub>2</sub> emissions	g/km	134

Technical data valid for ACEA countries/Some permitted weights valid only for Germany

<sup>&</sup>lt;sup>1)</sup> Height with roof aerial: 1462 mm <sup>2)</sup> Oil change volume